

Navigation

- [index](#)
- [modules](#) |
- [next](#) |
- [previous](#) |
- [Python v2.6.4 documentation](#) »
- [The Python Standard Library](#) »
- [9. Data Types](#) »

9.10. queue — A synchronized queue class¶

Note

The `Queue` module has been renamed to `queue` in Python 3.0. The [2to3](#) tool will automatically adapt imports when converting your sources to 3.0.

The `Queue` module implements multi-producer, multi-consumer queues. It is especially useful in threaded programming when information must be exchanged safely between multiple threads. The `Queue` class in this module implements all the required locking semantics. It depends on the availability of thread support in Python; see the [threading](#) module.

Implements three types of queue whose only difference is the order that the entries are retrieved. In a FIFO queue, the first tasks added are the first retrieved. In a LIFO queue, the most recently added entry is the first retrieved (operating like a stack). With a priority queue, the entries are kept sorted (using the [heapq](#) module) and the lowest valued entry is retrieved first.

The `Queue` module defines the following classes and exceptions:

`class Queue.Queue(maxsize)¶`

Constructor for a FIFO queue. `maxsize` is an integer that sets the upperbound limit on the number of items that can be placed in the queue. Insertion will block once this size has been reached, until queue items are consumed. If `maxsize` is less than or equal to zero, the queue size is infinite.

`class Queue.LifoQueue(maxsize)¶`

Constructor for a LIFO queue. `maxsize` is an integer that sets the upperbound limit on the number of items that can be placed in the queue. Insertion will block once this size has been reached, until queue items are consumed. If `maxsize` is less than or equal to zero, the queue size is infinite.

New in version 2.6.

`class Queue.PriorityQueue(maxsize)¶`

Constructor for a priority queue. `maxsize` is an integer that sets the upperbound limit on the number of items that can be placed in the queue. Insertion will block once this size has been reached, until queue items are consumed. If `maxsize` is less than or equal to zero, the queue size is infinite.

The lowest valued entries are retrieved first (the lowest valued entry is the one returned by `sorted(list(entries))[0]`). A typical pattern for entries is a tuple in the form: `(priority_number, data)`.

New in version 2.6.

`exception Queue.Empty¶`

Exception raised when non-blocking `get()` (or `get_nowait()`) is called on a [Queue](#) object which is empty.

`exception Queue.Full¶`

Exception raised when non-blocking `put()` (or `put_nowait()`) is called on a [Queue](#) object which is full.

See also

[collections.deque](#) is an alternative implementation of unbounded queues with fast atomic `append()` and `popleft()` operations that do not require locking.

9.10.1. Queue Objects¶

Queue objects ([Queue](#), [LifoQueue](#), or [PriorityQueue](#)) provide the public methods described below.

`Queue.qsize()¶`

Return the approximate size of the queue. Note, `qsize() > 0` doesn't guarantee that a subsequent `get()` will not block, nor will `qsize() < maxsize` guarantee that `put()` will not block.

`Queue.empty()¶`

Return `True` if the queue is empty, `False` otherwise. If `empty()` returns `True` it doesn't guarantee that a subsequent call to `put()` will not block. Similarly, if `empty()` returns `False` it doesn't guarantee that a subsequent call to `get()` will not block.

`Queue.full()¶`

Return `True` if the queue is full, `False` otherwise. If `full()` returns `True` it doesn't guarantee that a subsequent call to `get()` will not block. Similarly, if `full()` returns `False` it doesn't guarantee that a subsequent call to `put()` will not block.

```
Queue.put(item, block, timeout)
```

Put `item` into the queue. If optional args `block` is true and `timeout` is `None` (the default), block if necessary until a free slot is available. If `timeout` is a positive number, it blocks at most `timeout` seconds and raises the `Full` exception if no free slot was available within that time. Otherwise (`block` is false), put an item on the queue if a free slot is immediately available, else raise the `Full` exception (`timeout` is ignored in that case).

New in version 2.3: The `timeout` parameter.

```
Queue.put_nowait(item)
```

Equivalent to `put(item, False)`.

```
Queue.get([block, timeout])
```

Remove and return an item from the queue. If optional args `block` is true and `timeout` is `None` (the default), block if necessary until an item is available. If `timeout` is a positive number, it blocks at most `timeout` seconds and raises the `Empty` exception if no item was available within that time. Otherwise (`block` is false), return an item if one is immediately available, else raise the `Empty` exception (`timeout` is ignored in that case).

New in version 2.3: The `timeout` parameter.

```
Queue.get_nowait()
```

Equivalent to `get(False)`.

Two methods are offered to support tracking whether enqueued tasks have been fully processed by daemon consumer threads.

```
Queue.task_done()
```

Indicate that a formerly enqueued task is complete. Used by queue consumer threads. For each `get()` used to fetch a task, a subsequent call to `task_done()` tells the queue that the processing on the task is complete.

If a `join()` is currently blocking, it will resume when all items have been processed (meaning that a `task_done()` call was received for every item that had been `put()` into the queue).

Raises a `ValueError` if called more times than there were items placed in the queue.

New in version 2.5.

```
Queue.join()
```

Blocks until all items in the queue have been gotten and processed.

The count of unfinished tasks goes up whenever an item is added to the queue. The count goes down whenever a consumer thread calls `task_done()` to indicate that the item was retrieved and all work on it is complete. When the count of unfinished tasks drops to zero, `join()` unblocks.

New in version 2.5.

Example of how to wait for enqueued tasks to be completed:

```
def worker():
    while True:
        item = q.get()
        do_work(item)
        q.task_done()

q = Queue()
for i in range(num_worker_threads):
    t = Thread(target=worker)
    t.setDaemon(True)
    t.start()

for item in source():
    q.put(item)

q.join()          # block until all tasks are done
```

[Table Of Contents](#)

[9.10. queue — A synchronized queue class](#)

- [9.10.1. Queue Objects](#)

Previous topic

Next topic

This Page

- [Show Source](#)

Navigation

- [index](#)
- [modules](#) |
- [next](#) |
- [previous](#) |
- [Python v2.6.4 documentation](#) »
- [The Python Standard Library](#) »
- [9. Data Types](#) »

© [Copyright](#) 1990-2010, Python Software Foundation.

The Python Software Foundation is a non-profit corporation. [Please donate.](#)

Last updated on Feb 26, 2010. Created using [Sphinx](#) 0.6.3.