

Navigation

- [index](#)
- [modules](#) |
- [next](#) |
- [previous](#) |
- [Python v2.6.4 documentation](#) »
- [The Python Standard Library](#) »
- [36. Unix Specific Services](#) »

36.8. `tty` — Terminal control functions

Platforms: Unix

The `tty` module defines functions for putting the tty into cbreak and raw modes.

Because it requires the [termios](#) module, it will work only on Unix.

The `tty` module defines the following functions:

`tty.setraw(fd[, when])`

Change the mode of the file descriptor `fd` to raw. If `when` is omitted, it defaults to `termios.TCSAFLUSH`, and is passed to [termios.tcsetattr\(\)](#).

`tty.setcbreak(fd[, when])`

Change the mode of file descriptor `fd` to cbreak. If `when` is omitted, it defaults to `termios.TCSAFLUSH`, and is passed to [termios.tcsetattr\(\)](#).

See also

Module [termios](#)

Low-level terminal control interface.

[Previous topic](#)

[36.7. termios — POSIX style tty control](#)

[Next topic](#)

[36.9. pty — Pseudo-terminal utilities](#)

[This Page](#)

- [Show Source](#)

Navigation

- [index](#)
- [modules](#) |
- [next](#) |
- [previous](#) |
- [Python v2.6.4 documentation](#) »
- [The Python Standard Library](#) »
- [36. Unix Specific Services](#) »

© [Copyright](#) 1990-2010, Python Software Foundation.

The Python Software Foundation is a non-profit corporation. [Please donate.](#)

Last updated on Feb 26, 2010. Created using [Sphinx](#) 0.6.3.