

## Navigation

- [index](#)
- [modules](#) |
- [next](#) |
- [previous](#) |
- [Python v2.6.4 documentation](#) »
- [The Python Standard Library](#) »
- [21. Internet Protocols and Support](#) »

## 21.3. `cgitb` — Traceback manager for CGI scripts

New in version 2.2.

The `cgitb` module provides a special exception handler for Python scripts. (Its name is a bit misleading. It was originally designed to display extensive traceback information in HTML for CGI scripts. It was later generalized to also display this information in plain text.) After this module is activated, if an uncaught exception occurs, a detailed, formatted report will be displayed. The report includes a traceback showing excerpts of the source code for each level, as well as the values of the arguments and local variables to currently running functions, to help you debug the problem. Optionally, you can save this information to a file instead of sending it to the browser.

To enable this feature, simply add this to the top of your CGI script:

```
import cgitb
cgitb.enable()
```

The options to the `enable()` function control whether the report is displayed in the browser and whether the report is logged to a file for later analysis.

```
cgitb.enable([display[, logdir[, context[, format]]]])
```

This function causes the `cgitb` module to take over the interpreter's default handling for exceptions by setting the value of `sys.excepthook`.

The optional argument `display` defaults to `1` and can be set to `0` to suppress sending the traceback to the browser. If the argument `logdir` is present, the traceback reports are written to files. The value of `logdir` should be a directory where these files will be placed. The optional argument `context` is the number of lines of context to display around the current line of source code in the traceback; this defaults to `5`. If the optional argument `format` is `"html"`, the output is formatted as HTML. Any other value forces plain text output. The default value is `"html"`.

```
cgitb.handler([info])
```

This function handles an exception using the default settings (that is, show a report in the browser, but don't log to a file). This can be used when you've caught an exception and want to report it using `cgitb`. The optional `info` argument should be a 3-tuple containing an exception type, exception value, and traceback object, exactly like the tuple returned by `sys.exc_info()`. If the `info` argument is not supplied, the current exception is obtained from `sys.exc_info()`.

### Previous topic

[21.2. `cgi` — Common Gateway Interface support](#)

### Next topic

[21.4. `wsgiref` — WSGI Utilities and Reference Implementation](#)

### This Page

- [Show Source](#)

## Navigation

- [index](#)
- [modules](#) |
- [next](#) |
- [previous](#) |
- [Python v2.6.4 documentation](#) »
- [The Python Standard Library](#) »
- [21. Internet Protocols and Support](#) »

© [Copyright](#) 1990-2010, Python Software Foundation.

The Python Software Foundation is a non-profit corporation. [Please donate.](#)

Last updated on Feb 26, 2010. Created using [Sphinx](#) 0.6.3.